

# **Cement Mill Test Report**

Date of Issue: November 12, 2021

Plant: Exshaw, AB

Product: Portland Cement Type III

Mill Test Report Number: MTR-III-2021-10
Manufactured: October 1-31, 2021

# ASTM C 150-20 and AASHTO M 85-18 Standard Requirements

#### CHEMICAL ANALYSIS PHYSICAL ANALYSIS Spec limit **Test Result Item** Spec limit Test Result Rapid Method, X-Ray (C114) Air content of mortar (%) (C185) 12 max SiO<sub>2</sub> (%) 19.5 Blaine Fineness (m<sup>2</sup>/kg) (C204) Al<sub>2</sub>O<sub>3</sub> (%) 3.9 607 Fe<sub>2</sub>O<sub>3</sub> (%) 3.7 CaO (%) 62.0 Passing 45 µm (%) (C430) 99.0 4.5 MgO (%) 6.0 max Autoclave Expansion (%) (C151)\*\* 3.2 0.80 max SO<sub>3</sub> (%) 3.5 max 0.05 Loss on Ignition (%) 3.5 max 2.3 Insoluble Residue (%)\*\* 1.5 max 0.39 Compressive strength (MPa, [psi]) (C109) CO<sub>2</sub> (%) 1.7 1 day 12.0 [1740] min 25.7 [3730] Limestone (%) 5.0 max 4.2 3 days 24.0 [3480] min 35.5 [5150] CaCO<sub>3</sub> in Limestone (%) 28 days (Reflects previous month's data) 70 min 48.2 [6990] 94 **Inorganic Process Addition** 5.0 max (Lafarge Cement Kiln Dust) Time of setting (minutes) Adjusted Potential Phase Composition (C150) Vicat Initial (C191) 45 - 375 65 C<sub>3</sub>S (%) 56 C2S (%) 14 C<sub>3</sub>A (%) 4 15 max C<sub>4</sub>AF (%) 11 ASTM C 150-17 and AASHTO M 85-17 Optional Chemical Requirements:

ASTM C 150-17 and AASHTO M 85-17 Optional Chemical Requirements: NaEq (%) 0.60 max 0.56

We certify that the above described cement, at the time of shipment, meets the chemical and physical requirements of ASTM C 150-20 & AASHTO M 85-18 STANDARD SPECIFICATIONS FOR TYPE III CEMENT; and ASTM C 150-20 & AASHTO M 85-18 OPTIONAL CHEMICAL REQUIREMENTS FOR TYPE III LOW ALKALI CEMENT.

Certified By:

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, T0L 2C0 Phone: 403-673-3815

Lorraine Richards
Quality Control Coordinator

Lorraine Richards



# **Cement Mill Test Report**

Date of Issue: November 12, 2021

Plant: Exshaw, AB

Product: Portland Cement Type III

Mill Test Report Number: MTR-III-2021-10
Manufactured: October 1-31, 2021

## ASTM C 150-20 and AASHTO M 85-18 Standard Requirements

#### **Additional Data**

Item	Test Result	
	Limestone	Inorganic Process Addition
		Lafarge Cement Kiln Dust
Amount (%)	4.2	-
SiO <sub>2</sub> (%)	3.2	n/a
Al <sub>2</sub> O <sub>3</sub> (%)	1.1	n/a
Fe <sub>2</sub> O <sub>3</sub> (%)	0.4	n/a
CaO (%)	50.1	n/a
SO <sub>3</sub> (%)	0.2	n/a
CO <sub>2</sub> (%)	41.2	n/a

### **Base Cement Phase Composition**

Item	Test Result
C <sub>3</sub> S (%)	58
C <sub>2</sub> S (%)	14
C <sub>3</sub> A (%)	4
C <sub>4</sub> AF (%)	12

We certify that the data above reflects the materials used in cement manufacture during the production period indicated.

Note: Specifc Gravity for Portland Cements is 3.15

Certified By:

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, TOL 2C0

Phone: 403-673-3815

Lorraine Richards

Lorraine Richards
Quality Control Coordinator