

Cement Mill Test Report

Date of Issue: February 15, 2022

Plant: Exshaw, AB

Product: Portland Cement Type III

Mill Test Report Number: MTR-III-2022-01
Manufactured: January 1-31, 2022

ASTM C 150-20 and AASHTO M 85-18 Standard Requirements

CHEMICAL ANALYSIS			PHYSICAL ANALYSIS			
Item	Spec limit	Test Result	Item	Spec limit	Test Re	sult
Rapid Method, X-Ray (C114))		Air content of mortar (%) (C185)	12 max	5	
SiO ₂ (%)		19.6				
Al ₂ O ₃ (%)		4.0	Blaine Fineness (m ² /kg) (C204)		622	
Fe ₂ O ₃ (%)		3.7				
CaO (%)		62.1	Passing 45 μm (%) (C430)		99.1	
MgO (%)	6.0 max	4.4				
SO ₃ (%)	3.5 max	3.3	Autoclave Expansion (%) (C151)**	0.80 max	-0.06	
Loss on Ignition (%)	3.5 max	2.3				
Insoluble Residue (%)**	1.5 max	0.40	Compressive strength (MPa, [psi]) (C109)			
CO ₂ (%)		1.7	1 day	12.0 [1740] min	28.7	[4160]
Limestone (%)	5.0 max	3.9	3 days	24.0 [3480] min	40.2	[5830]
CaCO ₃ in Limestone (%)	70 min	96	28 days (Reflects previous month's data)		51.4	[7450]
Inorganic Process Addition	5.0 max	-				
(Lafarge Cement Kiln Dust)						
			Time of setting (minutes)			
Adjusted Potential Phase Composition (C150)			Vicat Initial (C191)	45 - 375	69	
C ₃ S (%)		54				
C ₂ S (%)		15				
C ₃ A (%)	15 max	4				
C ₄ AF (%)		11				
ASTM C 150-17 and AASHTO	•	•	ments:			
NaEq (%)	0.60 max	0.54				

We certify that the above described cement, at the time of shipment, meets the chemical and physical requirements of ASTM C 150-20 & AASHTO M 85-18 STANDARD SPECIFICATIONS FOR TYPE III CEMENT; and ASTM C 150-20 & AASHTO M 85-18 OPTIONAL CHEMICAL REQUIREMENTS FOR TYPE III LOW ALKALI CEMENT.

Certified By:

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, TOL 2C0

Phone: 403-673-3815

Lorraine Richards
Quality Control Coordinator

Lorraine Richards



Cement Mill Test Report

Date of Issue: February 15, 2022

Plant: Exshaw, AB

Product: Portland Cement Type III

Mill Test Report Number: MTR-III-2022-01
Manufactured: January 1-31, 2022

ASTM C 150-20 and AASHTO M 85-18 Standard Requirements

Additional Data

Item	Test Result		
	Limestone	Inorganic Process Addition	
		Lafarge Cement Kiln Dust	
Amount (%)	3.9	-	
SiO ₂ (%)	1.5	n/a	
Al ₂ O ₃ (%)	0.7	n/a	
Fe ₂ O ₃ (%)	0.3	n/a	
CaO (%)	51.5	n/a	
SO ₃ (%)	0.2	n/a	
CO ₂ (%)	42.4	n/a	

Base Cement Phase Composition

Item	Test Result
C ₃ S (%)	57
C ₂ S (%)	16
C ₃ A (%)	4
C ₄ AF (%)	12

We certify that the data above reflects the materials used in cement manufacture during the production period indicated.

Note: Specifc Gravity for Portland Cements is 3.15

Certified By:

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, TOL 2C0

Phone: 403-673-3815

Lorraine Richards

Lorraine Richards
Quality Control Coordinator