

Cement Mill Test Report

Date of Issue: May 12, 2023

Plant: Exshaw, AB

Product: Portland Cement Type HE

Manufactured: April 1-30, 2023

CHEMICAL ANALYSIS			PHYSICAL ANALYSIS		
Item	Spec limit	Test Result	Item	Spec limit	Test Result
Rapid Method, X-Ray					
SiO2 (%)		19.3			
Al2O3 (%)		4.0	Blaine Fineness (m2/kg)		535
Fe2O3 (%)		3.5			
CaO (%)		61.8	Retained 45 um (%)		0.7
MgO (%)	5.0 max	4.7			
SO3 (%)	3.5 max **	3.2	Autoclave expansion (%)*	1.0 max	0.12
Loss on ignition @ 950 (%)	3.0 (3.5) max ***	2.6			
Loss on ignition @ 550(%)	3.0 max	0.6	Compressive strength (MPa)		
Insoluble residue (%)*	1.5 max	0.3	1 day	13.5 min	24.9
			3 day	24.0 min	36.8
			28 day (March 2023 Results)		48.7
Inorganic Process Addition	5.0 max	-			
(Cement Kiln Dust)			Time of setting (minutes)		
			Vicat Initial	45 - 375	80
Potential Phase Composition					
C3S (%)		64	Mortar Bar Expansion (%) (C5)*	0.020 max	0.010
C2S (%)		7			
C3A (%)		5	Colour (For Information Purposes O	nly)	31
C4AF (%)		11			

Other Chemical Information:

NaEq (%) 0.57

We certify that the above described cement, at the time of shipment, meets the chemical and physical requirements of the applicable specification for Type HE.



CSA A3001-18 STANDARD SPECIFICATIONS FOR TYPE HE CEMENT.

Lafarge Canada Inc. - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB TOL 2C0

Phone: 403-673-3815

Certified By:

Lorraine Johnson

Lorraine Johnson Quality Manager

^{*} Latest available value

^{**} May exceed 3.5% SO3 maximum based on our A3004-C5 results of <0.020% expansion at 14 days.

^{***} May exceed 3.0% LOI maximum based on our LOI at 550C <3.0%.