

#### Cement

### **FLY ASH TEST REPORT**

Analysis by: Lafarge Seattle Concrete Lab

Sample from : Centralia Power Plant

Average Analysis: March 2024 Test Report Number 4-24 F CSA

# **Chemical Analysis**

			Limits
Silicon Dioxide (SiO <sub>2</sub> )	48.4	%	
Aluminum Oxide (Al <sub>2</sub> O <sub>3</sub> )	18.0	%	
Iron Oxide (Fe <sub>2</sub> O <sub>3</sub> )	5.9	%	
Sulphur Trioxide (SO <sub>3</sub> )	1	%	
Calcium Oxide (CaO)	14.5	%	15% Max - CSA
Magnesium Oxide	4.1	%	
Moisture Content	0.2	%	
Loss on Ignition	0.47	%	
Total Alkalies as Equivalent Na <sub>2</sub> O	4.60	%	

## **Physical Analysis**

Fineness Retained on 45 um (No. 325 Sieve)	11.3	%	34% Max - CSA
Strength Activity Index with Portland Cement			
% of Control at 28 Days (previous month's result)	108	%	
Water Requirement, Percent of Control	93	%	
Density	2.67	Mg/m <sup>3</sup>	

We hereby certify that the composite fly ash sample above meets the chemical and physical requirements of CAN/CSA A3001 for Type F Fly Ash.

Certified

Rob Shogren Technical Director

### WESTERN REGION

5400 West Marginal Way SW, Seattle, Washington 98106-1517 Office: 206.923.0098 or 800.477.0100 Fax: 206.923.0388