



Cement Mill Test Report

Month of Issue: May 2024

Plant: Richmond, British Columbia

Product: Portland Cement Type GUL / MSL

Mill Test Report # R-GUL-24-05
Manufactured: April 2024

CSA A3000:23 Standard Requirements

| CHEMICAL ANALYSIS | | | PHYSICAL ANALYSIS | | |
|--------------------------------|------------|-------------|--|------------|-------------|
| Item | Spec limit | Test Result | Item | Spec limit | Test Result |
| Rapid Method, X-Ray | | | Air content of mortar (%) (C 185) | | 6.0 |
| SiO2 (%) | | 18.4 | | | |
| Al2O3 (%) | | 4.6 | Blaine Fineness (m2/kg) | | 434 |
| Fe2O3 (%) | | 3.0 | , - | | |
| CaO (%) | | 62.9 | Passing 45 um (%) | 72 min | 99.0 |
| MgO (%) | | 0.9 | | | |
| SO3 (%) | 3.0 max* | 2.7 | Compressive strength (MPa) | | |
| Loss on ignition @ 950 (%) | 10.0 max | 6.6 | | | |
| | | | 3 days | 14.5 min | 29.2 |
| Insoluble residue (%) | | 0.24 | 7 days | 20.0 min | 37.0 |
| Free Lime (%) | | 1.0 | 28 days (Reflects previous month's data) | 26.5 min | 45.8 |
| Inorganic Process Addition (%) |) | 3 | , | | |
| . 3 (, | | | Time of setting (minutes) | | |
| | | | Vicat Initial | 45-375 | 110 |
| Potential Phase Composition* | | | | | |
| C3S (%) | | 73 | | | |
| C2S (%) | | 21 | Sulphate Resistance (C6) | 0.05 | 0.04 |
| C3A (%) | | 7 | ` ' | | |
| C4AF (%) | | 9 | Colour (L*) | | 64 |
| • • | | | Cement Density | | 3.09 |

*Corrected by using ASTM Calculation for Limestone Cement

We certify that the above described cement, at the time of shipment, meets the chemical and physical requirements of applicable specifications for Type GUL / MSL CSA A3000:23 STANDARD SPECIFICATIONS FOR TYPE GUL / MSL CEMENT; Cement complies with NSF 61

Western BU - Richmond 7611 No 9 Rd Richmond, BC 604 244 4300

NaEq (Alkali) (%)

Questions or enquiries can be directed to Paul Deram
Paul Deram
Lafarge - Technical Services Engineer
7591 #9 Road, Richmond, BC, V6W 0A6 Canada
C +1 604 690 8872
E paul.deram@lafarge.com

Robyn van Zutphen Quality Manager 5/21/2024

Certified By: