

Cement Mill Test Report

Date of Issue: October 15, 2024

Plant: Exshaw, AB

Product: Portland Cement Type III
Mill Test Report Number: ESW_Type III 2024-9
Manufactured during the month of: September 2024

ASTM C 150-22 and AASHTO M 85-22 Standard Requirements

CHEMICAL ANALYSIS PHYSICAL ANALYSIS Spec limit **Test Result** Spec limit ltem **Test Result** Rapid Method, X-Ray (C114) Air content of mortar (%) (C185) 12 max 6 SiO₂ (%) 194 Blaine Fineness (m²/kg) (C204) Al₂O₃ (%) 4.1 487 Fe₂O₃ (%) 3.4 CaO (%) 61.6 Passing 45 μm (%) (C430) 99.3 MgO (%) 6.0 max 4.6 Compressive strength (MPa, [psi]) (C109) SO₃ (%) ** 3.5 3.5 max Loss on Ignition (%) 2.5 12.0 [1740] min 20.3 [2939] 3.5 max 1 day 24.0 [3480] min Insoluble Residue (%) 1.5 max 0.3 3 days 31.3 [4537] CO₂ (%) 1.9 28 days (Previous Month's Result) 50.1 [7265] Limestone (%) 5.0 max 4.4 CaCO₃ in Limestone (%) 70 min 96.0 Inorganic Process Addition 5.0 max Time of setting (minutes) (Lafarge Cement Kiln Dust) Vicat Initial (C191) 45 - 375 77 Adjusted Potential Phase Composition (C150) Mortar Bar Expansion (%) (C1038) 0.020 max 0.009 C₃S (%) 54 C2S (%) 15 C₃A (%) 15 max 5 C₄AF (%) 10

ASTM C 150-22 and AASHTO M 85-22 Optional Chemical Requirements:

Na₂Oeq (%) Weekly Averages: Week 1 0.56 Week 2 0.57 Week 3 0.55 Week 4 0.59 Max 0.60

** May exceed 3.0% SO3 maximum based on C1038 results of <0.020% expansion at 14 days.

We certify that the above described cement, at the time of shipment, meets the chemical and physical requirements of:

ASTM C 150-22 & AASHTO M 85-22 STANDARD SPECIFICATIONS FOR TYPE III CEMENT; and ASTM C 150-22 & AASHTO M 85-22 OPTIONAL CHEMICAL REQUIREMENTS FOR TYPE III LOW ALKALI CEMENT.

Exceptions: C430 is excluded from the scope of the AASHTO accreditation.

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, T0L 2C0

Phone: 403-673-3815

Certified By:

John W Blair Quality Manager



Cement Mill Test Report

Date of Issue: October 15, 2024

Plant: Exshaw, AB

Product: Portland Cement Type III
Mill Test Report Number: ESW_Type III 2024-9
Manufactured: September 2024

ASTM C 150-22 and AASHTO M 85-22 Standard Requirements

Additional Data

Item	Test Result	
	Limestone	Inorganic Process Addition
		Lafarge Cement Kiln Dust
Amount (%)	4.4	-
SiO ₂ (%)	2.5	n/a
Al ₂ O ₃ (%)	0.5	n/a
Fe ₂ O ₃ (%)	0.2	n/a
CaO (%)	48.6	n/a
SO ₃ (%)	0.1	n/a
CO ₂ (%)	42.3	n/a

Base Cement Phase Composition

Item	Test Result
C ₃ S (%)	56
C ₂ S (%)	15
C ₃ A (%)	5
C ₄ AF (%)	11

Specific Gravity (For Information Purposes Only) 3.17

We certify that the data above reflects the materials used in cement manufacture during the production period indicated.

Western Canada BU - Exshaw Plant P.O. Box 160, Highway 1A, Exshaw AB, T0L 2C0

Phone: 403-673-3815

Certified By:

John W Blair Quality Manager