

#### Cement

# **FLY ASH TEST REPORT**

Analysis by: Lafarge Seattle Concrete Lab

Sample from : Centralia Power Plant

Average Analysis: November 2024 Test Report Number 12-24 F CSA

### **Chemical Analysis**

		Limits
Silicon Dioxide (SiO <sub>2</sub> )	49.7 %	
Aluminum Oxide (Al <sub>2</sub> O <sub>3</sub> )	17.9 %	
Iron Oxide (Fe <sub>2</sub> O <sub>3</sub> )	<b>5.9</b> %	
Sulphur Trioxide (SO <sub>3</sub> )	0.9 %	
Calcium Oxide (CaO)	13.9 %	15% Max - CSA
Magnesium Oxide	4.0 %	
Moisture Content	0.09 %	
Loss on Ignition	0.36 %	
Total Alkalies as Equivalent Na₂O	4.20 %	

# **Physical Analysis**

Fineness Retained on 45 um (No. 325 Sieve)	13.1	% 34% Max - CSA
Strength Activity Index with Portland Cement		
% of Control at 28 Days (previous month's result)	103	%
Water Requirement, Percent of Control	91	%
Density	2.61	Mg/m <sup>3</sup>

We hereby certify that the composite fly ash sample above meets the chemical and physical requirements of CAN/CSA A3001 for Type F Fly Ash.

Certified :

Rob Shogren Technical Director

### WESTERN REGION

5400 West Marginal Way SW, Seattle, Washington 98106-1517 Office: 206.923.0098 or 800.477.0100 Fax: 206.923.0388